

1325



Tally DASCOM's 1325 flat-bed serial dot matrix printer, is a 24 pin, 80 column printer with USB and parallel interfaces as standard. The 1325 is ideal for front office applications in retail outlets, travel agents, train stations, banks and doctor's surgeries where space is limited.

With high quality output, an easy to use control panel and the option to use pre-cut or tractor fed paper, the 1325 is ideal for counter-top printing applications such as, tickets, receipts, forms and multi-part documents.

Highlights at a glance:

- Compact 24-pin flat-bed printer
- Up to 375 characters per second
- Ideal for front office applications
- Auto switching USB and parallel interface
- Long life ribbon
- Small footprint

The long life ribbon of the 1325 means fewer ribbon changes, less downtime and lower running costs. With print speeds of 375 characters per second (cps) and flexible media handling it keeps transactions smooth and the user happy.

The 1325 is a reliable and easy to use printer, with low running costs and a space saving size.

Configurations:




- **1325** Standard Product

1325

Print Speed	375 cps (Fastest Draft); 250 cps (Draft), 82 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	273 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead Life	400 million characters
Memory	92 kB
Standard Connectivity	Parallel (Bi-directional) and USB 2.0
Standard Emulation	IBM 2390 Plus+, Epson LQ (ESC P/2)
Fonts	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 10 Barcodes
Consumables	Ribbon: 7 million characters
Standard Paper Handling	Push tractor for continuous paper with straight paper path, Cut sheet from the front
Number of Copies	1 original + 6 copies
Paper Type	Cut sheets, Continuous forms, multi-part forms
Paper Weight	52-100 g/m ²
Paper Size	Width: 55 to 297 mm (Cut Sheet)
Physical Weight	5 kg
Physical Size	404 x 322 x 203 mm (W x D x H)
Acoustic	53 dB(A)
Power Voltage	230 V - 50/60 Hz
Power Consumption	5,9 Watt Stand-By
Temperature	0° to +40° C; 10% to 90% humidity
Workload	6.000 pages per month
MTBF	10.000 hours
Drivers	Windows 2000/XP/Vista/7/8 and Server 2003/2008

The Printer Place
800-243-3338
2221 South Dupont Drive
Anaheim, CA 92806

www.theprinterplace.com

SERIAL MATRIX PRINTERS 
MOBILE PRINTERS 
FLATBED PRINTERS 
THERMAL PRINTERS 