

Matrix Printer

2600+ High performance at low cost







HIGHLIGHTS AT A GLANCE

- Print speed up to 683 cps
- Up to 20.000 pages/month
- 24 wires printhead for excellent print quality
- Straight paper path for easy paper handling
- Metal tear bar
- Ethernet with IPv6 suppirt, parallel and USB interface as standard
- USB Host interface for easy firmwareupdate
- Userfiendly, backlight illuminated LC display



2600+

The new Tally Dascom 2600+ is the further developed variant of the successful Tally Dascom 2600.

Thanks to the two-part upper cover, the printed pages can now be removed even more easily from the end of the book. A **metal tear bar** ensures that even thicker paper or multiple sets are separated cleanly. The **durable ribbon for 10 million characters** can easily be replaced. The new ribbon mask ensures that the ribbon is inserted correctly. In addition to the standard interfaces **USB**, **Parallel and Ethernet** (with IPv6 support), the Tally Dascom 2600+ now also has a **USB host interface**, so that new firmware can easily be installed with the help of a USB stick.

The new print head is not only up to 20% faster, but also allows for a noise reduction of up to 2 decibels thanks to its design.

TECHNICAL DATA

| Print speed | 683 cps (Fastest Draft); 600 cps (HS-Draft), 513 cps (Draft), 114 cps (LQ) bei 10 cpi |
|--------------------------|--|
| Resolution | Up to360 x 360 dpi |
| Throughput (ECMA 132) | 457 pages per hour |
| Character density | 10, 12, 15, 17.1, 20 cpi |
| Line density | 2, 3, 4, 6, 8, 12 lpi |
| Printhead lifetime | 500 Mio. impact per wire |
| RAM | 256 kB |
| Interface Standard | Parallel (Bi-directional), USB 2.0 and Ethernet (10/100BaseT, IPv6) USB Host |
| Interface Optional | Serial RS-232 |
| Administration | Tally WebPanel via Ethernet; Config-Tool via USB/Parallel |
| Emulations Standard | IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP Epson FX 9-Nadel Emulation |
| Fonts | HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing |
| Consummables | Ribbon: 10 Mio. characters |
| Paper handling Standard | One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off |
| Papier handling Optional | Additional push tractor (rear) |
| Copies | Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copies |
| Paper types | Cut sheets, continuous forms, multi-part forms |
| Paper weight | 60-120 g/m ² |
| Paper format | Width: 76 to 278 mm; Length: 76 to 599 mm |
| Weight | 8,1 kg |
| Dimensions | 458 x 265 x 200 mm (W x D x H) |
| Noise | <53 dB(A) |
| Voltage | 100 - 240 V autosensing |
| Power consumption | 60 Watt printing; <3 W Sleep Mode |
| Temperatur e | +10° to +40° C; 10% to 85% rel. humidity |
| Print volume | 20.000 pages per month |
| MTBF | 20.000 hours |
| Driver | Windows 7/8/10 and Server 2008/2012 (32/64 Bit); SAP |
| | |

Configuration:

• 2600+ Standard model

The Printer Place 800-243-3338 2221 South Dupont Drive Anaheim, CA 92806 www.theprinterplace.com

All company and product names are trademark of theri respective owner. Copyright © 2017 DASCOM. Specification are subject to change without notice. Subject to modification, of error or misprint.

