

2610





The Tally Dascom 2610 is a highly featured, reliable and stylish machine. Performance and workload, ergonomics, maintainability, excellent price — everything has been incorporated to ensure it is the only acceptable choice for the business users.

Continuous and cut forms are fed from the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier; the operator does not have to fumble over or around the printer to gain access to rear located tractors.

Highlights at a glance:

- Print speeds up to 667 cps
- 20,000 pages per month workload
- 136 columns
- 24 pin print head produces excellent print quality
- 9-Pin emulation to replace printers on old legacy systems
- Straight through paper path for easy forms loading
- Ethernet, parallel and USB interfaces as standard
- LC Display for easy operation

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, warehouse, manufacturing floor or in the office. An unobtrusive 55 dBA acoustic rating results in a printer, which is double as quiet, compared with many competitive models.

With the build-in Epson FX emulation this printer is also able to replace old legacy 9-pin printing systems.

Configurations:

• 2610

Standard Product





2610

Print Speed	667 cps (Fastest Draft); 600 cps (Ultra-Draft), 333 cps (Draft), 111 cps (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million dots per wire
Memory	256 kB
Standard Connectivity	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT)
Optional Connectivity	Serial RS-232
Standard Emulation	IBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCP, Epson FX 9-Pin
Optional Emulation	LA-Upgrade Kit with DEC ANSI PPL2
Administration	Tally WebPanel
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes
	and large character printing
Consumable	Ribbon: 15 million characters
Standard Paper Handling	One tractor useable as push (front or rear) or pull (top) version, continuous paper
	with straight paper path and park position, cut sheet front insertion, tear or front off
Optional Paper Handling	Additional push tractor (rear)
Number of Copies	Push tractor front: 1 original + 5 copies;
	Pull tractor top: 1 original + 5 copy;
	Cut sheet: 1 original + 5 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 76 to 420 mm; Length: 76 to 599 mm
Physical Weight	10,6 kg
Physical Size	600 x 265 x 200 mm (W x D x H)
Acoustic	< 55 dB(A)
Power Voltage	100 - 240 V wide range auto-sensing
Power Consumption	40 Watt Printing; <10 W Sleep Mode
Temperature	+10° to +40° C; 10% to 85% humidity
Workload	20.000 pages per month
MTBF	20.000 hours
Drivers	Windows 7/8/10 and Server 2008/2012; SAP

The Printer Place 800-243-3338 2221 South Dupont Drive Anaheim, CA 92806 SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS