

DT-230 Thermal POS Receipt Printer



Highlights at a glance:

- High Speed Printing
- Easy Paper Loading
- Flexible interfaces including WiFi
- Supports ESC/POS emulation
- Heavy duty cutter standard
- Supports pages mode printing

Dascom's DT-230 POS direct thermal printer offers reliability, precision and performance in a small footprint, where space is limited.

The user friendly design of the printer allows a space saving easy cover opening and an easy to load print Mechanism.

The clearly labeled panel enables simple and effective operation making it very easy to use.

The mechanism is designed with robust construction ensuring reliable operation, a must for all transaction environments.

The DT-230 offers a wide range of connectivity options allowing use with both an installed base of equipment and complete new installations.

With wired and wireless interfaces, the DT-230 can be installed in the most difficult space configurations.

The external power supplies make it easy to inventory your POS printer for operation in all parts of the world.

The DT-230 is appropriate for use in many vertical industries, including retail, hospitality and food service, and healthcare.

Available Connectivity Configurations:




- USB and Cash Drawer standard on all units
- Serial available
- Parallel available
- Ethernet available
- WiFi available

DT-230

Print Speed	260 m/sec
Print Width	72 mm, 576 dots - Font A 46 Chars/line, Font B 64 Chars/line
Print Method	Direct Thermal Line Printing, Friction Feed
Media Width	80mm or 58mm paper width
Resolution	203 dpi, 8dots/mm
Printhead Life	150km
Memory	RAM: 1Mbytes; Flash: 4Mbytes
Standard Connectivity	USB and Cash Drawer
Optional Connectivity	Serial, Parallel, Ethernet and WiFi
Emulation	ESC/POS
Character Sets	PC437, PC850, PC852, PC858, PC860, PC863, PC865, PC866, KU42, TIS11, TIS18, PC720
Roll Max External Dia.	83 mm
Roll Core Dia.	13 mm
Physical Weight	Approximately 1.8kg
Physical Size	147×198×146 (L×W×H mm)
Power Voltage	AC 100-240V/50-60Hz, DC 24V±5%, 2.1A
Operating Temperature	5-45°C, 41-113°F
Humidity	10-95%
Cutter	2,000,000 cuts
Options	Splash Cover, wall hanging plate
Drivers	MS Win XP Pro, Win Vista Bus., Win 7 Pro 32/64, Linux
Warranty	Two year return to depot

The Printer Place
800-243-3338
2221 South Dupont Drive
Anaheim, CA 92806
www.theprinterplace.com

Copyright 2012 © DASCOM Americas Corporation All rights reserved.
Specifications are subject to change without notice

SERIAL MATRIX PRINTERS 
MOBILE PRINTERS 
FLATBED PRINTERS 
THERMAL PRINTERS 