

## T2340



*Tally*

DASCOM's mid range serial matrix printers include the T2340 series products. Very popular transaction printers, they feature great ergonomics. Forms are easy to load as the paper's installed at the front, not the rear. With automatic top of form and zero tear the printers are easy to set up with no wasted forms.

The products are ideal for back office applications which include retail, local government, hospitals, warehousing and ditribution. They include printing labels, shipping documents and multipart forms.

### Highlights at a glance:

- **High quality 9 and 24 pin printhead**
- **136 columns**
- **Front feed for easy paper loading and reliable paper transport**
- **Zero tear, paper park, automatic top of form for ease of use**
- **Wide range of emulations for easy connection to a wide range of hosts**
- **Manual feed: front in, front out; ideal for cheques, statements, registration cards**

Both 9 and 24 pin models are available for different print quality requirements; narrow and wide format machines offer the choices of small footprint and diverse range of forms.

In line with market demands, the new printers are quieter and easier to use than competitive products in their class. All products support graphics and barcodes.

### Configurations:

- **T2340/9** 9 pin version/136 column
- **T2340/24** 24 pin version/136 column

## T2340

<b>Print Speed</b>	500 cps (Fastest Draft); 413 cps (Draft), 77 cps (NLQ) at 10 cpi (9 pin) 440 cps (Fastest Draft); 409 cps (Draft), 92 cps (LQ) at 10 cpi (24 pin)
<b>Resolution</b>	up to 144 x 240 (9 pin) up to 360 x 360 dpi (24 pin)
<b>Throughput</b> (ECMA 132)	363 pages per hour (9 pin) 368 pages per hour (24 pin)
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	300 million characters
<b>Memory</b>	64 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional)
<b>Standard Emulation</b>	IBM ProPrinter , EpsonFx, MTPL + Barcode (9 pin) IBM ProPrinter XL, Epson LQ850+, MTPL + Barcode (24 pin)
<b>Fonts</b>	HS Draft, Draft, Courier, Quadrato (9 pin) HS Draft, Draft, Roman, Sans Serif, Prestige, Elite, Script, OCR-A/B (24 pin)
<b>Consumables</b>	Ribbon: 4 million characters
<b>Standard Paper Handling</b>	Push tractor and cut sheet insertion
<b>Optional Paper Handling</b>	2 <sup>nd</sup> Push tractor
<b>Number of Copies</b>	1 original + 5 copies (9 pin) 1 original + 3 copies (24 pin)
<b>Paper Type</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 76 to 255 mm; Length: 76 to 559 mm
<b>Physical Weight</b>	11 kg
<b>Physical Size</b>	625 x 245 x 200 mm (H x W x D)
<b>Acoustic</b>	54 dB(A) (9 pin) 53 dB(A) (24 pin)
<b>Power Voltage</b>	230 V - 50/60 Hz
<b>Power Consumption</b>	55 Watt Printing
<b>Temperature</b>	+10° to +35° C; 20% to 80% humidity
<b>Workload</b>	14.000 pages per month
<b>MTBF</b>	12.500 hours
<b>Drivers</b>	Windows 2000/XP/Vista/7/8 and Server 2003/2008; SAP