

T2380 LPR (Line Printer Replacement)

The Printer Place - Les Brown
2140 South Dupont Drive
Anaheim, CA 92806
(800) 243-3338
sales@theprinterplace.com



Tally

Highlights at a glance:

- Full range of automatic features to **minimize** user intervention
- Ideal for 'On-Demand' applications with Zero Tear for **no loss of forms**
- Straight through paper path for **easy forms loading**
- Parallel and Ethernet (10/100BaseT) standard.
- Optional Interfaces: Coax/Twinax/IPDS; Ethernet IPDS
- **Compatible** with a wide range of operating systems including Windows, UNIX, SAP R3 and legacy systems like Open VMS

Cost of Operations

- Initial Hardware and Maintenance costs are lower than Line Printers

Features and Advantages

- Use current Programs / same Printer Parameters for easy replacement
- **Load Multiple Forms:** the T2380 -2T LPR has **Front** and **Rear** loading
- **Auto-Gap:** automatically sets the correct print gap based on form thickness
- **Easy-to-navigate Menu** structure: from **Control Panel** or **Web Browser**
- **Durability:** in Harsh, rugged environments including dirty, dusty warehouses
- **Tabletop:** space saving
- **Service options:** Onsite - Next Business Day, Express Exchange
- **Expert Tech Support:** – supports your business with the ultimate in rapid response and convenience
- **Yearly and Multi-year Service Contracts:** which can be customized to fit your needs
- **New Genuine OEM Parts:** used in every repair, guaranteed
- **Long Life Ribbon:** easy to install, clean-hands, 50 mil character Ribbon cartridge
- **Quality Control of Ribbons:** meeting stringent specifications to ensure superior performance.

Dascom T 2380 LPR - Desktop (smaller footprint), Ethernet, True Zero Tear, Multiple Forms loading

Serial Impact
Printers

Mobile Printers

Thermal Printers

Connectivity

Consumables

Service

Available Configurations:

T2380 LPR Standard	PN - 302019
T2380 LPR Standard with Stand	PN - 302020
T2380 LPR -2T	PN - 302026
T2380 LPR -2T with Stand	PN - 302027

T2380 LPR (Line Printer Replacement)

Print Speed	1.000 cps (Fastest Draft); 800 cps (Draft), 222 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput	(ECMA 132) 680 pages per hour
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	750 million strokes per pin
Standard Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Ethernet 10/100 BaseT
Optional Connectivity	RS-232 Serial, Ethernet with IPDS, Coax/Twinax with SCS or IPDS
Standard Emulation	MT660, IBM ProPrinter III XL, Epson FX , Genicom ANSI, HP2564c, P6000
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes, and scaleable Large Character Printing
Graphics	QMS® CODE V™ Version 2; Printronix® PGL
Consumables	Ribbon: 50 million characters
Standard Paper Handling	Push tractor for continuous paper with straight paper path, Zero Tear off and park position
Optional Paper Handling	Additional push tractor (front), Automatic cutting device
Number of Copies	Push tractor front: 1 original + 5 copies Push tractor rear: 1 original + 3 copies (2T version)
Paper Type	Continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 3" to 16.5"; Length: 3" to 22"
Physical Weight 1	9 kg
Physical Size	24.5" x 17" x 11" mm (W x D x H)
Acoustic	59 dB(A)
Power Voltage	120 V or 230 V, 50 or 60 Hz (Auto-Switching)
Power Consumption	70 Watt Printing; 18 W Power-Save
Temperature	+10° to +35° C; 20% to 80% humidity (not condensing)
Workload	50.000 pages per month
MTBF	12.500 hours
Warranty	90 days on-site warranty

Note For OCR applications it is recommended that your readers are tested. Paper is a highly variable medium and should be tested prior to purchase.

The Printer Place - Les Brown
2221 South Dupont Drive
Anaheim, CA 92806
(800) 243-3338
sales@theprinterplace.com