

T5040



Tally

With up to 600 characters per second, the T5040 rapidly processes media of diverse types ranging from passbooks and cheques to A5 receipts and A4 information sheets.

The printer's flatbed design provides totally assured paper handling, and with advanced features such as Automatic Paper Alignment and Auto Gap Adjustment (AGA), they offer unsurpassed ease-of-use. Using Serial Impact technology - the most reliable and versatile method available of producing print - the T5040 is a durable, robust, dependable printer that supports a wide range of printing applications.

Highlights at a glance:

- Supports a wide variety of media
- Automatic gap adjustment of the print head
- Automatic alignment of forms and passbooks
- Automatic edge detection
- Ability to connect to multiple hosts simultaneously via parallel or USB, plus an optional second serial port
- Unrivalled transaction times - typical passbook 2.2 seconds
- DIN Letter 11.8 seconds

The standard T5040 supports cut forms via a serial interface connection and a secure command language, as demanded within the banking environment. As standard, USB and Parallel interfaces are included for flexibility of connection and single-station, multi-user operation. A second, plug in, serial interface is available as an upgrade option.

Also available are models with Magnetic Stripe encoding for reading accounts codes directly into the system minimizing user intervention.

Configurations:




- **T5040** Standard Product
- **T5040 MSR-H** with horizontal magnetic stripe reader

T5040

Print Speed	600 cps (Fastest Draft); 400 cps (Draft), 133 cps (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Character Density	10, 12, 15, 16.6, 17.1, 20 cpi
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead Life	400 million characters
Memory	256 kB
Standard Connectivity	Parallel (Bi-directional), Serial RS-232 and USB 2.0
Standard Emulation	IBM 4722, IBM ProPrinter XL24E, Epson LQ (ESC P/2), Olivetti PR50/PR2/PEe
Fonts	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 10 Barcodes
Consumables	Ribbon: 10 million characters
Standard Paper Handling	Cut sheet from the front with automatic alignment
Number of Copies	1 original + 4 copies
Paper Type	Cut sheets, multi-part forms, passbooks with a thickness up to 2,0 mm
Paper Weight	60 - 260 g/m ²
Paper Size	Width: 70 to 240 mm; Length: 70 to 500 mm (cut sheet) Width: 105 to 235 mm; Length: 125 to 210 (passbooks)
Physical Weight	9,5 kg
Physical Size	378 x 280 x 168 mm (W x D x H)
Acoustic	55 dB(A)
Power Voltage	230 V - 50/60 Hz
Power Consumption	73 W Printing; 9 Watt Stand-By
Temperature	+10° to +40° C; 15% to 75% humidity
Workload	5.000 transactions per month
MTBF	10.000 hours
Drivers	Windows 2000/XP/Vista/7/8 and Server 2003/2008

The Printer Place
800-243-3338
2221 South Dupont Drive
Anaheim, CA 92806

www.theprinterplace.com

SERIAL MATRIX PRINTERS 
MOBILE PRINTERS 
FLATBED PRINTERS 
THERMAL PRINTERS 