

2600



Tally
DASCOM

The Tally Dascom 2600 is a highly featured, reliable and stylish machine. Performance and workload, ergonomics, maintainability, excellent price – everything has been incorporated to ensure it is the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors.

Highlights at a glance:

- Print speeds **up to 680 cps**
- **20,000 pages per month** workload
- 80 columns
- 24 pin print head produces excellent print quality
- **Straight through paper path** for easy forms loading
- Ethernet, parallel and USB interfaces standard
- **LC Display** for easy operation

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52 dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Configurations:

- **2600** Standard Product

2600

Print Speed	680 cps (Fastest Draft); 500 cps (HS-Draft), 333 cps (Draft), 111 cps (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million dots per wire
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT)
Optional Connectivity	Serial RS-232
Standard Emulation	IBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCP
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing
Consumable	Ribbon: 6 million characters
Standard Paper Handling	One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off
Optional Paper Handling	Additional push tractor (rear),
Number of Copies	Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 1 copy; Cut sheet: 1 original + 5 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in
Physical Weight	8,6 kg, 18.9 lbs
Physical Size	458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)
Acoustic	52 dB(A)
Power Voltage	100 - 240 V wide range auto-sensing
Power Consumption	40 Watt Printing; <10 W Sleep Mode
Temperature	+10° to +40° C; 10% to 85% humidity
Workload	20.000 pages per month
MTBF	15.000 hours
Drivers	Windows 2000/XP/Vista/7/8 and Server 2003/2008; SAP