

ODV-2D Inline Barcode Verifier

Compliant Verification • Data Validation • Fully Integrated • Standalone Operation



Benefits of Our ODV-2D Printers



Eliminate expensive compliance fees by producing 100% accurate barcodes, 100% of the time.

The ODV-2D is the industry's first affordable, fully integrated solution with the ability to print, verify, and validate 1D and 2D barcodes. The ODV-2D installs on either the T8000 or T6000e printers. It is the first system that grades barcodes to ISO 15415, 15416 and 15426 standards and stores a detailed report of each transaction. Our exclusive technology reads each barcode, identifies a rejected barcode, and reprints a replacement label without operator intervention. The ODV-2D pays for itself by eliminating costly charge backs and fines for non-conforming labels. Advanced features allow it to integrate easily and quickly into existing applications.



Compliant Verification

- Verifies full suite of 1D & 2D barcodes with up to 50 barcodes per label
- Performs both data validation and compliance verification
- Grades to ISO standards including Quiet Zone & Check Sum errors
- Label back-up and overstrike to identify bad barcodes
- Barcode "GPS" dynamically locates barcodes on a label by label basis to improve throughput



Productivity

- Prints and verifies at up to 8ips
- ODV-2D can read 1D and 2D barcodes in any 90° orientation
- PrintNet Enterprise Auto ID provides global or enterprise wide network access, control, update and reporting
- Compatible with third party label software through PXML data reporting
- Most extensive suite of printer emulations in the industry



Dependable Design

- Field kits available for both T8000 and T6000e printers
- Easy installation and setup
- No requirement for scheduled calibration or maintenance
- Calibration check from printer's control panel using provided plaque
- Works with a wide variety of label and ribbon types

Tired of Rejected Shipments and Non-Compliance Fees?

With a global increase in regulatory compliance standards and fines, it is more important than ever to ensure your products are labeled correctly with accurate barcodes. ODV-2D addresses these requirements with the ability to validate and verify up to 50 barcodes per label INCLUDING 2D barcodes.

The ODV-2D reads and grades every barcode on every label based on ISO standards. When ODV-2D rejects a barcode, it overstrikes the label and reprints it without operator intervention. At the end of the day you can generate a report directly from the printer with data on every label printed and graded. Archive that data and you'll never pay compliance fees again!



Full Overstrike Example
(T8000 ODV-2D)



Partial Overstrike Example
(T6000e ODV-2D)

Combining Verification with Validation

The ODV-2D can verify and validate barcodes as they are printed. The data printed on the label is validated to match the data sent from the host (native commands only). The barcode image is verified to comply with the ISO standards.

Manage Your Entire Enterprise from a Single Location

Printronix AutoID Data Manager (part of the PrintNet Enterprise Suite) gives you the ability to dynamically record, archive and generate reports of scanned barcode data for every printer on your network. With the addition of our robust printer management tool, you can pull reports for your entire enterprise as well as monitor and configure printers from anywhere in the world. You can also designate events and be alerted to printer issues via email. PrintNet Enterprise is available at no charge.

Closed-Loop Application Design

Printronix' integration of ODV into the printer not only enables the printer to backup and overstrike bad labels without operator intervention, but provides the application access to the data from the ODV, including grading reports as well as label images. Data from ODV can be passed back to the application in .csv or PXML format, enabling the label software to not only send labels to the printer, but can check each label to ensure that the correct data was printed and the label barcodes grades were acceptable. This data can be captured, merged with the print job information, and an image of the label can be captured as well and also archived with the ODV grading report for future reference.

Software partners such as TEKLYNK already use this application connection to provide a close-loop label quality process.



ODV-2D Series | Data Sheet



Model	T8000 ODV-2D	T6000e ODV-2D
Print Speed (ips)	8	8
Print Width (in)	4	4
Print Resolution (dpi)	203/300	203/300/600
Back-up and Overstrike	6 in	1 in
Max Barcodes per label	50	50
Maximum Label Length (in)	24	24
Media Handling	Tear/Peel/Cut	Tear/Peel
Dual Vision / RFID function	No	Yes
Printer Footprint (L / W / H)	22 x 11.7 x 13	22 x 10.9 x 12.3
Barcode 2D	Datamatrix, QR, PDF417	Datamatrix, QR, PDF417
Read Technology	Camera	Camera
ISO Compliance	Yes	Yes
Scan Resolution (mils)	2	2
Minimum X-Dimension 1D (mils)	10	10
Minimum X-Dimension 2D (mils)	10	10
Barcode Support	1D, 2D	1D, 2D
Barcode GPS	Yes	Yes
Barcode Orientation	0°, 90°, 180°, 270°	0°, 90°, 180°, 270°
OCR	Perceptor PTXL	No
OCR Point Size	5pt	No
Fonts	Arial (others available upon request)	No
Characters	Upper Case, Numbers	No
OCV / Blemish Detect / Pattern Match / Duplicate Check	Perceptor PTXL	No
Output Reports	Yes	Yes
Remote Config / Mgmt	Yes	Yes
Data Report Capture	Yes	Yes
Cloud Database	Perceptor PTXL	No

For more information on ODV or label quality inspection, please contact your local Printronix Auto ID sales representative.



Perceptor PTXL trademark is owned by InterVision Global Group | perceptor-ptxl.com



The Printer Place | 800-243-3338 | theprinterplace.com | service@theprinterplace.com
2221 South Dupont Drive | Anaheim, CA 92806