

T2380



Tally

"Unsurpassed excellence." This defines the rugged high-powered T2380 Printer. Built to leave a lasting impression on your productivity, this high-speed workhorse exemplifies what rugged durability is all about.

With its advanced 24-pin print head, the T2380 is engineered to perform at a blistering pace even in the harshest operating environments.

You're assured of top-shelf performance, crisp, clear and reliable print quality at a low running cost.

You can count on the T2380 when your performance is what counts and you want value and dependability.

Highlights at a glance:

- Full range of automatic features to minimize user intervention
- Ideal for "On-Demand" and "Batch" applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100 Base T) standard
- Optional Interfaces: RS-232 Serial; Coax/Twinax; Ethernet IPDS
- Compatible with a wide range of operating systems including Windows, Unix, DOS, SAP R3 and legacy systems

These products are well matched to Microsoft Windows applications and are highly compatible with other host operating environments including legacy systems.

Fully automated operations, coupled with a straight through paper path allows ease of use and virtually eliminates errors caused by user intervention.

In addition, these printers comply with Intelligent Mail Barcode, a US postal standard that is a required capability to ensure you receive the best available postage rate.

Make sure when choosing a printer, it has this feature.

Intelligent Mail Barcode sample



SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS

CONNECTIVITY

CONSUMABLES

Available Configuration:

- **T2380** Standard Product
- **T2380 2T** with additional rear tractor

T2380

Print Speed	1,000 cps (Fastest Draft); 800 cps (Draft), 22 cps (NLQ) at 10 cpi
Resolution	Up to 360 x 360 dpi
Throughput (ECMA 132)	680 pages per hour
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	750 million strokes per pin
Standard Memory	128 kB
Standard Connectivity	Parallel (Bi-Directional IEEE 1284) and Ethernet (10/100 Base T)
Optional Connectivity	RS_232 Serial, Ethernet with SCS or IPDS, Coax/Twinax and SCS or IPDS
Standard Emulation	Epson LQ (ESC P/2), IBM Proprinter XL24e, MTPL + Barcodes, Genicom ANSI
Optional Emulation	PCL 3 (Rugged Writer), IGP/PGL, Code V, MT660, Printronix P6000, HP2564c
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scaleable Large Character Printing
Consumables	Ribbon: 20 million (standard)
Standard Paper Handling	Push Tractor for continuous paper with straight paper path, Tear off and Park position.
Optional Paper Handling	Additional Push Tractor (front), Automatic Cutting Device
Number of Copies	Push Tractor (Front) 1 original + 5 copies Push Tractor (Rear) 1 original + 3 copies (2T version)
Paper Type	Continuous Forms, Multi-Part Forms (.025" thick max.)
Paper Weight	60 - 120 g/m ²
Paper Size	Width: 3" to 16.5"; Length: 3" to 22"
Physical Weight	Approximately 45.6 lbs. (20.7 kg)
Physical Size	24.5" x 17" x 11" (W x D x H)
Acoustic	59 db(A)
Power Voltage	120 or 240 (V) (auto-switching)
Power Consumption	70 (W) Printing; 18 (W) Power-Save
Temperature	+ 50 to +95 F; 20% to 80% humidity (not condensing)
Workload	50,000 pages per month
MTBF	12,500 hours
Warranty	90 days On-Site Warranty
Drivers	Windows 2000/XP/Vista/7/8/10 and Server 2003/2008/2012; SAP
Note	For OCR applications it is recommended that your readers are tested. Paper is a highly variable medium and should be tested prior to purchase.

DASCOM Americas Corporation

The Printer Place

800-243-3338

2221 South Dupont Drive

Anaheim, CA 92806

www.theprinterplace.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 