

# **T6000**

HIGH-PERFORMANCE THERMAL PRINTER

SPEED

VERSATILITY

RELIABILITY







## The Powerful T6000 represents the next generation industrial, high-performance thermal barcode printer.

Setting new benchmarks for speed, print quality, validation and reliability, the T6000 is engineered with the singular mission of increasing true productivity and lowering compliance fees. Loaded with advanced features, validation technology, RFID capabilities and the most comprehensive emulation package available, the T6000 delivers supercharged performance for a wide array of applications.



#### SPEED

- Stellar quality print at lighting fast speed, clocking in at 14 ips
- Increased productivity at every shift as a direct result of the ARM Cortex-A9 controller, processing barcode data faster than ever before
- Ease-of-Use and an interactive screen reduces training and down time, helping your business focus on operational productivity



#### VERSATILITY

- Plug-n-Play in any operational environment, with the ability to be networked via the most comprehensive printer emulations in the industry
- Rugged design allows the T6000 to perform in even the most challenging environmental conditions
- Wide-ranging RFID support for On-Pitch, Short-Pitch and Standard Pitch to handle a variety of applications



#### RELIABILITY

- Exclusive validation solutions eliminate expensive compliance fees by producing 100% quality barcodes, 100% of the time
- Comprehensive WiFi security suite featuring the very latest protocols to block unauthorized access and ensure peace of mind
- Intelligent heat management system increases printhead life and improves barcode print quality while reducing operating costs

### REAL WORLD BUSINESS APPLICATIONS THAT GIVE YOU THE EDGE ON YOUR COMPETITORS

- With industry-leading validation technologies like ODV that support the latest compliance labeling requirements your supply chain is now fortified with cutting-edge traceability applications that also eliminate costly compliance fines
- Easy integration in any legacy environment with full provisions for any Warehouse Management System helping you increase uptime and prevent loss of productivity
- Powers through the most rigorous shifts while handling multiple label applications- from 'Pick and Pack' support and cross-docking applications to labels for cases, pallets, packages, shipment slips, invoices, etc.

### POSTSCRIPT/PDF FOR YOUR MOST COMPLEX LABELING NEEDS

- The T6000 is engineered to support all major ERP systems
- Plug-n-Play with native SAP drivers to expand your operational abilities
- Full range of fonts and symbols gives you the tools required to customize your labels to suit your unique application and environment

#### **PRINTNET ENTERPRISE AUTO ID:**

- Printronix Auto ID provides a unique remote printer management tool to monitor, configure and support printers from anywhere in the world
- Instant email and mobile phone alerts allow you to mitigate issues or designate events in real-time, maintaining continuous network health and peak performance
- Fully compatible with any Printronix Auto ID product

#### **GENUINE PRINTRONIX SUPPLIES:**

Our commitment to your particular application does not end at your printer. Instead, our promise of reliability continues throughout the life of your application and with every single printout. Genuine Printronix Supplies meet the stringent performance standards required by our printers and ensure optimum performance at every shift, every single day. With extensive manufacturing capabilities and multiple distribution points, our product experts can deliver custom solutions for a wide variety of applications.

SAY GOODBYE TO BAD BARCODES. With compliance fines as high as \$10,000, it is more critical than ever to print clean, readable barcodes. Online Data Validator (ODV) reads every barcode as it's printed. And if there is an error, the printer strikes through the bad barcode and reprints a new one.



## **T6000** SPECIFICATIONS

#### **PRODUCT BENEFITS**

- High performance ARM Cortex-A9
- Die-cast aluminum frame w/metal door
- Transfer and direct printing
- 4" and 6" model configurations
- Premium Asian and Andale font support

#### PRINTER SPECIFICATIONS

Max Print Speed (4"/6") Print Method Resolution Max. Print Width Printer Memory

#### MEDIA SPECIFICATIONS

Media Type Min. Media Width (4"/6") Max. Media Width Min, Media Length Max. Media Length Media Thickness Media Roll Core Diameter Max. Media Roll Diameter Media Sensing

#### **RIBBON SPECIFICATIONS**

Ribbon Type Coating Min. Ribbon Width (4"/6") Max. Ribbon Width (4"/6") Max. Ribbon Length

#### PHYSICAL CHARACTERISTICS

Width (4"/6") Height (4"/6") Depth (4"/6") Printer Weight (4"/6") Shipping Weight (4"/6")

#### PRINTER LANGUAGE

IGP Languages Job Control Languages **Optional Languages** 

42.6 lbs. (18.6Kg)/48 lbs. (21.5Kg) PGL/VGL/ZGL/TGL/IGL/STGL/DGL/IEGL/MGL PJL, XML, and PTX-SETUP IPDS TN5250

State-of-the-art WiFi connectivity

Available in 203 DPI and 300 DPI

ENERGY STAR Certified

14/12 IPS @ 203 DPI; 12/10 IPS @ 300 DPI

Roll or Fan-Fold Labels, Tags, Paper, Film, Tickets

0.25" / 1.0" (Continuous/Tear-Off) / 1.0" (Peel-Off)

\*

Transfer and Direct 203 DPI / 300 DPI

4.1" (104mm) / 6.6" (168mm)

512MB RAM / 128MB Flash

1" (25.4mm)/2" (50.8mm)

Up to 99"

8.0" (209mm)

Wax, Wax/Resin, Resin

1" (25.4mm)/2" (50.8mm

Gap, Mark

450 Meters

4.5" (114.3mm) / 6.8" (172.7mm)

2.5 Mil (0.0025") to 10 Mil (0.010")

1.5" (37.5mm) to 3.0" (76mm)

Coated side in. coated side out

4.5" (114.3mm)/6.8" (172.7mm)

10.9" (276.9mm)/14.1" (358.1mm) 12.3" (312.4mm)/12.4" (314.9mm)

20.3" (515.6mm)/20.3" (515.6mm)

33.6 lbs. (14.5Kg)/39 lbs. (17.4Kg)

PDF Level 1.7, Postscript Level 3

512MB RAM / 128MB Flash Memory

4-32 GB SD memory card capability

#### COMMUNICATION AND CONNECTIVITY/INTERFACE

Standard Interface I/O Optional Interface I/O WiFi Security Protocol

Serial RS232, USB, and Ethernet 10/100Base T Parallel, WiFi (802.11a/b/g/n), GPIO WEP 40/128bit, WPA Personal (PSK), WPA2 Personal (PSK) and Enterprise (AES CCMP) EAP-TLS, EAP-TTLs, PEAPv0/MS-CHAPv2, PEAPv1 EAP-MD5

#### **MEDIA HANDLING MODES**

Standard Options

Continuous, Tear-Off Strip, Tear-Off Peel-Off, Cut, and Rewind











#### **BARCODE VALIDATION**

BARCODE VALIDATION	
Online Data Validator (ODV)	Validates, Grade, Report, and Overstrike bar codes Supports 1D Barcodes (Picket Fence) Compatible with RFID encoding
RFID	
UHF EPC Gen2 / ISO18000-6C	Multi-position RF antenna, Advanced Printer Encoder Firmware encodes and validates Gen2 compliant tags On-Pitch label to 0.625 in (depending on inlay) PGL, ZPL, STGL, MGL language support Counters track good / bad label encoding
OPERATING ENVIRONMENT	
Operating Temperature Operating Humidity Storage Temperature Storage Humidity	40 to 104 °F (5 to 40 °C) 20 - 85% Non-Condensing 23 to 140 °F (-5 to 60 °C) 5 - 85% Non-Condensing
POWER REQUIREMENT	
Line Input	Auto Range 100 - 264 VAC (48 - 62 Hz)
REGULATORY COMPLIANCES	
Emissions Safety Environmental Radios (WiFi/RFID)	FCC, CE, CCC cTUVus, CE, EAC, SABS, RCM, CCC, KCC, S-MARK, NOM RoHS, WEEE, Energy Star FCC, CE, IC, and others based on market need
BAR CODE SYMBOLOGIES	
1D Barcodes 2D Barcodes	BC-412, Code 11, Code 39, Code 35, Code 93, Codabar Code128 Subsets A/B/C, Industrial 2 of 5, Interleave 2 of 5, German I-2/5, EAN-8, EAN-13, UCC/EAN-128, UPC-A, UPC-E, UPCSHIP, UPS 11, MSI, Matrix 2 of 5, PLESSEY, POSTNET, 4-state PostBar, Australian 4-state, FIM, ITF14, TELEPEN, PLANET, USPS Intelligent Mail, LOGMARS PDF-417, MicroPDF-417, Maxicode, DataMatrix, QR Codes, Aztec, GS1 Databar (RSS-14)
FONT, GRAPHIC SUPPORT	
Graphic Formats Font Technologies Standard Fonts Asian Fonts (Optional SD card) Andale Fonts (Optional SD card) PDF/ PostScript Level 3	PCX, TIFF, BMP, PNG Intellifont, TrueType, Unicode OCRA, OCRB, Courier, Letter Gothic, CG Times, CG Triumvirate/Bold/Condensed Simplified Chinese, Japanese, and Korean Simplified Chinese, Traditional Chinese, Korean, Japanese 35 Fonts
REMOTE MANAGEMENT SOFTWARE	
PrintNet Enterprise Auto ID	Enterprise Grade Remote Management Solution
OPTIONS AND ACCESSORIES	
<ul> <li>WiFi 802.11 a/b/g/n (US/EU/CAN)</li> <li>Parallel Port</li> <li>GPIO</li> <li>TN5250</li> <li>PDF/PostScript</li> <li>IPDS</li> </ul>	<ul> <li>Rewind 4"/6"</li> <li>Heavy Duty Cutter 4"/6"</li> <li>Peel &amp; Present 4"/6"</li> <li>Premium Asian Font Cards</li> <li>Andale Font Cards</li> <li>QCMC (SD Quick Change Memory Card)</li> </ul>
* Online Date Validates (ODV)	

\* UHF RFID (US 902-928MHz, EU 866-868MHz)

IPDS \* Online Data Validator (ODV)



2221 South Dupont Drive Anaheim, CA 92806 800-243-3338 sales@theprinterplace.com www.theprinterplace.com