

# Ribbons for TTP-286MT • TTP-384MT

- Compliance Labeling For Shipping & Receiving
- Pallet Labeling
- Inventory Control Labeling
- Drum Labeling
- Custom Signage






# Ribbons available for TSC TTP-286MT, TTP-384MT


Supported by a full range of ink formulations, you can be confident that your Genuine TSC ribbon will meet the demands of your label printing application.

Enjoy consistent, premium quality and optimized performance through your TSC printer.

#### **SWX - TSC Standard Wax**



## **PWX - TSC Premium Wax**




- Widely used for barcode application. Provides excellent print quality.
- Suitable for standard labeling applications
- Compatible with most coated and non-coated paper labels

Your P/N	35-W130600-20CA	35-W154600-20CA	35-W165600-20CA	35-W170600-20CA	35-W220600-20CA
No. rolls/Box	6	6	6	6	6
Length (m)	600	600	600	600	600
Width (mm)	130	154	165	170	220


- Resin-enhanced wax
- Best scratch and smudge resistance for a wax ribbon
- Supports high speed printing
- Excellent print quality on all papers and some film materials

Your P/N	35-W130600-20CB	35-W154600-20CB	35-W165600-20CB	35-W170600-20CB	35-W220600-20CB
No. rolls/Box	6	6	6	6	6
Length (m)	600	600	600	600	600
Width (mm)	130	154	165	170	220

### **SWR - TSC Standard Wax/Resin**



**PWR - TSC Premium Wax/Resin** 




- General purpose wax/resin formulation
- Superior print quality on all common papers and films. Our most versatile formulation.
- Good scratch and smudge resistance

Your P/N	•	35-S154600-20CC		35-S170600-20CC	35-S220600-20CC
No. rolls/Box	6	6	6	6	6
Length (m)	600	600	600	600	600
Width (mm)	130	154	165	170	220


- Designed to print on a wide range of coated papers and films
- Very sharp print quality, enabling ladder and rotated barcode printing simultaneously
- Enhanced abrasion and scratch resistance

_	ength (m)	600	600	600	600	600
Y	our P/N	35-S130600-20CD	35-S154600-20CD	35-S165600-20CD	35-S170600-20CD	35-S220600-20CD

### **SRE – TSC Standard Resin**



### **PRE - TSC Premium Resin**



- Excellent mechanical resistance, including abrasion and scratch
- Extensive adaptability to a wide range of film materials
- Supports higher print speeds

Your P/N	35-R130600-20CE	35-R154600-20CE	35-R165600-20CE	35-R170600-20CE	35-R220600-20CE
No. rolls/Box	6	6	6	6	6
Length (m)	600	600	600	600	600
Width (mm)	130	154	165	170	220

- Designed for the most extreme environmental conditions
- Highest abrasion, scratch and solvent resistance
- Compatible with a wide range of synthetic materials

Your P/N	35-R130600-20CF	35-R154600-20CF	35-R165600-20CF	35-R170600-20CF	35-R220600-20CF
No. rolls/Box	6	6	6	6	6
Length (m)	600	600	600	600	600
Width (mm)	130	154	165	170	220