

1140



The Tally Dascom 1140, is a 9 pin, 80 column serial dot matrix printer with a USB interface as standard. Compact in size, the 1140 is perfect for industrial environments and front and back office applications where space is limited.

With low running costs, high quality output and an easy to use control panel it's ideal for small business, low volume listings and reports, as well as dispatch notes and labels.

Highlights at a glance:

- Compact 9-pin narrow carriage printer
- Up to 400 characters per second
- Ideal for front and back office applications
- Variety of interfaces
- Long life ribbon
- Small footprint
- Energy Star Approved

In addition to these applications, the 1140 is also well suited to measurement and control systems. Among the lowest priced matrix printers available today, the 1140 also offers a long life ribbon giving this printer very low running costs.

For draft printing it's considerably less expensive operating costs make it a viable alternative to low end inkjet printers.

Configurations Available:

Part Number	Description
288830504	1140 Printer, 9 pin, 80 Col - 110/240v, USB
288830510	1140 Printer, 9 pin, 80 Col - 110/240v, USB and Parallel
288830511	1140 Printer, 9 pin, 80 Col - 110/240v, USB and Serial
99007	Ribbon, Tally Dascom 1140

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

1140

Print Speed	400 cps (Fastest Draft); 300 cps (Draft), 75 cps (NLQ) at 10 cpi
Resolution	up to 144 x 240 dpi
Throughput	290 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	1, 2, 3, 4, 6, 8 lpi
Print Head Life	400 million strokes
Memory	up to 256 kB
Standard Connectivity	USB 2.0
Optional Connectivity	Parallel IEEE 1284. Serial RS-232C
Standard Emulation	IBM ProPrinter 2380 Plus, Epson ESC P/2
Fonts/Barcodes	Draft, Quadrato, Courier, HS Draft, OCR-A/B, EAN-8, EAN-13, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
Consumables	Ribbon: 9 million characters
Standard Paper Handling	Push tractor and friction
Optional Paper Handling	Roll holder
Number of Copies	1 original + 4 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	52 - 100 g/m ²
Paper Size	Width: 95 to 267 mm, 9.75 to 10.5 in., Length: 114 to 362 mm, 4.5 to 14.25 in. (Cut sheet); 114 to 558 mm (4.5 to 22.0 in) (Fanfold)
Physical Weight	5 kg, 11 lbs
Physical Size	369 x 283 x 130 mm, 14.5 x 11.1 x 5.1 in., (W x D x H)
Acoustics	57 dB(A)
Power Voltage	100-240 V - 50/60 Hz
Power Consumption	less then 1.2 Watt Sleep Mode
Temperature	+5° to +35° C; 41° to 95° F 10% to 80% humidity
Workload	6,000 pages per month
MTBF	12.000 hours
Drivers	Windows Vista/7/8.1 and Server 2008/2012
Warranty	One year return to depot

Note:

For OCR applications, it is recommended that your readers are tested with sample printouts supplied by Dascom. Paper is a highly variable medium and should be tested prior to purchase.